
Perforce 2009.2

Getting Started with P4V

December 2009

This manual copyright 2005-2009 Perforce Software.

All rights reserved.

Perforce software and documentation is available from <http://www.perforce.com>. You may download and use Perforce programs, but you may not sell or redistribute them. You may download, print, copy, edit, and redistribute the documentation, but you may not sell it, or sell any documentation derived from it. You may not modify or attempt to reverse engineer the programs.

Perforce programs and documents are available from our Web site as is. No warranty or support is provided. Warranties and support, along with higher capacity servers, are sold by Perforce Software.

Perforce Software assumes no responsibility or liability for any errors or inaccuracies that may appear in this book.

By downloading and using our programs and documents you agree to these terms.

Perforce and Inter-File Branching are trademarks of Perforce Software. Perforce software includes software developed by the University of California, Berkeley and its contributors.

All other brands or product names are trademarks or registered trademarks of their respective companies or organizations.

Table of Contents

Basic Concepts.....	5
Connecting to a Server.....	6
Navigating the Main Screen.....	7
Setting up your workspace	8
Managing your Files	10
Getting files from the depot.....	10
Checking out files from the depot	11
Editing files in your workspace	11
Diffing files to view your edits.....	12
Discarding edits by reverting	12
Checking your edits into the depot	13
Displaying a file's revision history	14
Graphical Reporting Tools.....	14
Viewing file revisions as a diagram.....	15
Browsing file revisions using Time-lapse View	16
Displaying folder history using the folder diff tool	16
Important and Useful Features.....	17
Tooltips.....	18
Drag and drop.....	18
File views.....	18
Tearing off tabs	19
Setting Preferences	20
Migrating from P4Win	20
Next Steps	23


Getting Started with P4V

P4V, the Perforce Visual client, is Perforce's cross-platform graphical user interface. You can use P4V on Windows, Macintosh, UNIX and Linux computers and benefit from an identical interface regardless of platform. This introductory guide provides some Perforce basics and an orientation to P4V's layout and features. For more details about P4V, consult its online help. To learn more about Perforce, consult the user documentation on our Web site.

To use Perforce to manage files, you typically connect to a Perforce server using a client program like P4V. P4V enables you to check files in and out, and perform the various other necessary tasks. The following sections tell you how to perform basic tasks and point out powerful features and shortcuts.

Basic Concepts

P4V connects your computer to a Perforce *server* to move files between Perforce *depots* and your *workspace*, as shown below.



The definitions for these Perforce terms are as follows:


- **Workspace:** folders or directories on the client computer where you work on revisions of files that are managed by Perforce.
- **Client application:** P4V (or another Perforce client application), running on your computer, sending commands to the Perforce server and receiving results (files, status information, and so on).

- Server: the program that executes the commands sent by client programs, maintains depot files, and tracks the state of workspaces. The Perforce Server typically runs on a central machine, connected to client machines by the network.
- Depot: a file repository on the Perforce server. It contains all existing versions of all files ever submitted to the server. There can be multiple depots on a single server. The examples in this guide show a single depot.

Connecting to a Server

To gain access to your depots, you must connect to a server. To connect to a server:

1. Launch P4V. P4V displays the following connection dialog:




2. Specify the following settings (your Perforce administrator can provide you with this information)
 - Server: the name of the computer where your Perforce server is running.
 - Port: the port number assigned to the server
 - User: your Perforce user name
 - Password: your Perforce user password, if required.
 - Workspace: the name of your client workspace.

To display a list of existing users and workspaces, click **Browse**. (The server and port must be specified before clicking **Browse**.)

If you have incorrectly specified a server setting, P4V displays a message like the following:

```
Connect to server failed; check $P4PORT.  
TCP connect to bigserver failed.  
bigserver: host unknown.
```


3. To connect, click OK. P4V displays its main screen, as shown in the following figure.



The next section describes the main screen panes.

Navigating the Main Screen

The following figure points out the panes and important features of the main screen. To see what a button or screen element does, hold the mouse cursor over it. P4V displays a descriptive tooltip.




Setting up your workspace

Your Perforce administrator can do this for you, but it's advisable to learn a few important aspects of configuring your workspace, specifically (1) configuring the client root directory and (2) configuring the client view.

To define a workspace, choose **Connection > New Workspace...** and, when prompted, enter a name for the workspace. To edit your current workspace specification, choose **Connection > Edit Current Workspace...**


P4V displays the specification details in the lower portion of the right pane; for example:



View: enables you to restrict the depot files to which you have access. Set the view to ensure that you see only what you need to see.

Root: specifies the location on your computer under which Perforce stores copies of depot files. Specify a meaningful name, and make sure it's **not** set to your computer's root directory!

To display and set the client view graphically, click the **View** tab. Browse to desired files and folders and context-click to include them or exclude them from the client view, as shown in the following figure.



Managing your Files

To manage files using Perforce, you typically perform the following sequence of tasks:

1. Get files from the depot.
2. Check out files you need to edit.
3. Edit files.
4. Check in your changes.

The following sections provide details about these and other common file management tasks.

Getting files from the depot

To copy files from the depot to your workspace:

1. In the left pane, click the **Depot** tab.
2. Browse to the folder or file you want to retrieve.
3. Context-click the file or folder. To get the most recent version, choose **Get Latest Revision**. To get an older version, choose **Get Revision...** and specify the version you want.

In the Log pane, P4V displays a message like the following.

```
p4 sync //depot/Misc/manuals/...#head
    //depot/Misc/manuals/recommended_configuration.doc added c:\p4clients\bruno-1492\Misc\manuals\recommended_configuration.doc
    //depot/Misc/manuals/triggers.doc added c:\p4clients\bruno-1492\Misc\manuals\triggers.doc
    //depot/Misc/manuals/vendor_branches.doc added c:\p4clients\bruno-1492\Misc\manuals\vendor_branches.doc
Sync copied 3 files to workspace (including 3 that were added)
Sync removed no files from workspace
Sync completed with no warnings or errors.
```

In the left pane, note that the files display green dots, indicating that they are present in your workspace:  Before you can edit the file, however, you must check it out.

Checking out files from the depot

To check out a file in your workspace:

1. Browse to the desired file in the left pane Depot tab.
2. Context-click the file and choose **Check Out**.

In the Log pane, P4V displays a message like the following:

```
p4 edit //bruno-1492/Misc/manuals/recommended_configuration.doc
      //depot/Misc/manuals/recommended_configuration.doc#1 - opened for
      edit
Opened 1 files for edit
```

In the left pane, note that the file displays a red check mark, indicating that you checked it out:


Note that, when you check out a file, Perforce adds it to a *changelist*, which is a list of related files. You can use changelists to group related files, for example, all files that contain changes required to implement a new product feature. To view the changelist, choose **View > Pending Changelists** or click  in the toolbar.

Now you're ready to edit your files.


Editing files in your workspace

To edit a checked-out file, double-click it (or context-click it and choose **Open With**, then select the desired application). P4V launches the corresponding editing application. Make changes and save the file.

To select an application with which to open a file, choose **File>Open With>Choose Application**. Note that you can configure editors for different file types by choosing **Edit > Preferences...** and clicking the **Editors** tab.

Diffing files to view your edits

To enable you to see what changes you've made, you can compare (*diff*) your edited file with the version you checked out. To diff, context-click the checked-out file in the left pane and choose Diff **Against Have Revision**. P4V launches P4Diff, displaying the differences between the two files. For example:



Discarding edits by reverting

If you decide you want to discard your changes:


1. Context-click the file in the left pane and choose **Revert**. P4V displays a warning dialog.
2. Click **OK**. In the Log pane, P4V displays a message like the following:

```
p4 revert //depot/Misc/manuals/recommended_configuration.doc
revert complete. 1 file affected.
```


Checking your edits into the depot

To check your changed file into the depot, perform the following steps.

1. Display pending changelists: click  in the toolbar. P4V displays a list of pending changelists, as shown in the following figure. To display the files in a changelist, expand it



2. Double-click the changelist in which your file is open. P4V displays the details, as shown in the following figure.



3. Enter a description explaining the changes you made and click **Submit**. The Log pane displays a message confirming that your changelist was submitted, similar to the following.

```
Change 813 submitted.  
submit complete. 1 file affected.
```

Displaying a file's revision history

To view the changes made to a file or folder, context-click the file or folder and choose **File History** or **Folder History**. The history for the selected file or folder is displayed in the right pane. For example, the following figure shows the history of a folder, listing every submitted changelist that affected a file in the folder.

Revision	Changelist	Date Submitted	Submitted By	Filetype	Description
<i>/depot/Jam/MAIN/src/compile.c</i>					
..619	11/12/20...	earl	text		Fix jam's handling of empty {} blocks so that it can recognise OS/2 client port of mainline.
..602	10/30/20...	earl	text		Jam's local variables can now be initialized.
..596	10/24/20...	earl	text		Fix up compiler warnings from -Wall in jam.
..550	9/5/2001...	earl	text		Finally, fix the jam include bug, using the parser scheme that
..549	9/5/2001...	earl	text		Concurrent process support for NT.
..340	6/5/2000...	earl	text		Move jam debug levels around.
..331	5/23/200...	earl	text		First half of support for binding variables in actions: the
..313	5/13/200...	earl	text		Support for multiple :t's on jam rule invocation and access to the
..284	4/19/200...	earl	text		Support for "local" declarations in jam.
..277	4/2/2000...	earl	text		Jam support for "if \${A} != \${B}".
..272	3/19/200...	earl	text		Jam porting fixes for sun4.
..265	3/8/2000...	earl	text		Compare all elements in jam if statement.
..262	3/5/2000...	earl	text		Support for turning on a single debug level with -d in jam.
..248	2/1/2000...	earl	text		Fixed wild little Jam bug that trashed variable settings if
..185	9/29/199...	earl	text		Get all function declarations.
..137	5/2/1999...	earl	text		Leaves instead of gale.
9.120	3/9/1999...	earl	text		Mkdir rule, NOUPDATE rule.
8.93	2/16/199...	earl	text		Galew.
7.70	2/3/1999...	earl	text		New ALWAYS rule. Changed -t.
6.69	2/2/1999...	earl	text		EXIT.
5.63	1/23/199...	earl	text		Copyright info.
4.30	1/10/199...	earl	text		

Graphical Reporting Tools


P4V includes several valuable graphical reporting tools:

- Revision Graph: displays a diagram that shows the evolution of a selected file, including files related by branching operations.
- Time-lapse View: shows how the contents of a selected text file changed from revision to revision. You can easily sweep through revision ranges to locate passages of interest and see when they were created and how they changed.
- Folder diff tool: enables you to see how the contents of a folder changed.

The following sections provide more details about these tools.

Viewing file revisions as a diagram


To display the revision diagram for a file, context-click the file in the left pane and choose Revision Graph. P4V launches the tool, which displays a diagram like the following one.



This diagram shows you when the file was created and how it was branched, and enables you to view details about each version submitted to the depot and navigate through the graph using the navigation map. For more details about the information displayed in the revision graph, consult P4V online help.

Browsing file revisions using Time-lapse View

To browse the changes made to a text file, context-click the file in the left pane and choose **Time-lapse View**. P4V launches the utility, which displays a screen like the following one.



Change detail: shows text that has been added, changed, or deleted in a revision

Using Time-lapse View, you can sweep through all revisions of the file using the slider, noting when changes were made and who made them. Again, for details, consult P4V online help.

Displaying folder history using the folder diff tool


The folder diff tool enables you to see how the contents of a folder have changed: which files have been added, changed, or deleted. To view changes to a folder:

1. Context-click the folder in the left pane Depot or Workspace tab and choose **Folder History**. In the right pane, P4V lists changelists that affected the folder, for example:

Revision	Date	Submitter	Description
709	12/24/20...	dai	Upgrade to latest metrowerks on Beos -- the Intel one.
705	12/19/20...	earl	Put in fix for jam's NT handle leak.
694	12/15/20...	gale	Fix URL in a jam doc.
633	11/17/20...	earl	Radstone's lynx port.
632	11/15/20...	raj	More jam twiddling, for NT.
631	11/15/20...	earl	Linux x86 2.0 and linux exp 2.0 build 97.3/4586.
627	11/14/20...	earl	Handle platform variants better, by defining OSPLAT whenever we can.
625	11/12/20...	earl	More twiddlings to the jam, for final release.
624	11/12/20...	earl	Fix up html references.

2. To display the changes that occurred between two revisions of a folder, drag and drop one of the revisions on the other.

P4V displays the changes as shown in the following figure. This example shows that, between the selected revisions, a file was edited and checked in. File highlights are color-coded to indicate additions, changes, and deletions. Expand folders and scroll to locate changes of interest. To skip to the next or previous change, click the right and left arrows.



Important and Useful Features

Among the many features provided by P4V, the following are especially useful:

- Tooltips: to get more information about an object, place your mouse cursor over it. P4V displays a popup dialog containing more details.
- Drag and drop: P4V includes numerous drag and drop shortcuts for common operations.
- File views: P4V enables you to preview graphics files using thumbnails.
- Tear off windows: to create a separate window displaying a specification you want to keep on display, you can tear it off.

The following sections provide more details.

Tooltips

P4V provides tooltips for many objects on the screen. For example, to display the status of a file, hold the mouse cursor over the file in the left pane. P4V displays a tooltip like the following one.




Another example: to display a changelist description, click in the toolbar and hold the mouse cursor over the changelist in the right pane. There are tooltips for all the P4V buttons, too.

Drag and drop


P4V provides drag and drop shortcuts for common tasks. Drag and drop can simplify operations on large groups of files. For example, to check out all the files in a folder, drag the folder to a changelist. To diff two files, drag one to the other. For details about drag and drop shortcuts, refer to the P4V online help.

File views

If you use Perforce to manage graphics files, P4V's thumbnail views enable you to preview the files. To display thumbnails, click the Files tab in the right pane, then select the desired thumbnail size from the title bar.




P4V displays thumbnails as shown in the following example.



Tearing off tabs

To keep a tab open, you can undock it. For example, context-click a file and choose File History, then choose **Window > Undock Tab**. P4V opens a separate window for it, as shown in the following figure.



To restore it to the main window, choose **Window > Dock Window**.

Setting Preferences

To configure P4V, choose **Edit > Preferences**. The tabbed **Preferences** dialog is displayed. In particular, the **Editor** tab enables you to associate applications with file types, overriding any operating system associations. The Diff and Merge tabs enable you to configure external applications, in case you prefer tools other than those that are bundled with P4V.

Migrating from P4Win

If you're moving from P4Win to P4V, here's a list of equivalent operations to help you in your transition.

P4Win Menu Item	Menu	P4V Menu Item	Menu	Notes
Add to Source Control...	File	Mark for Add	Actions	Applies only to files in the Workspace Tree
Diff 2 Files, Folders or Revisions	File	Diff...	Tools	
Diff Client File vs. Depot File	File	Diff...	Tools	Or context-click on file and choose: Diff Against Have Revision
Explore	File	Show in>Explorer	File	
Integrate Using Filespec or Branchspec	File	Integrate...	Actions	
Open for Delete	File	Mark for Delete	Actions	
Open for Edit	File	Check Out	Actions	
Properties	File	Files in Folder	View	File properties are displayed in the Details pane at the bottom of the Files in Folder view

P4Win Menu Item	Menu	P4V Menu Item	Menu	Notes
Remove from Client	File	Remove from Workspace	Actions	
Rename	File	Rename/Move...	Actions	
Revision History...	File	History	View	Alternatively context click on file and choose File History
View File...	File	Open	File	Alternatively context click on file and choose Open
Check Consistency	File>More	Reconcile Offline Work...	Actions	Applies only to folders in the Workspace Tree
Auto Resolve...	File>Resolve	Resolve...	Actions	
Interactively... [Resolve]	File>Resolve	Resolve...	Actions	
Schedule File for Resolve	File>Resolve	Get Latest Revision	Actions	
Sync to Head Revision	File>Sync	Get Latest Revision	Actions	
Sync...	File>Sync	Get Revision...	Actions	
Find File Matching Pattern...	Edit	Find File...	Edit	
Find File Under Selected Folder...	Edit	Find File...	Edit	
Bookmarks	View	Bookmarks	Tools	

P4Win Menu Item	Menu	P4V Menu Item	Menu	Notes
Client View of Depot	View	Depot Tree	View	Restrict to client view by choosing: View>Filter Depot>Tree Restricted to Workspace View
ClientSpecs	View	Workspaces	View	
Entire Depot	View	Depot Tree	View	Show the entire depot by choosing: View>Filter Depot>Entire Depot Tree
Local View of Client Tree	View	Workspace Tree	View	
Show Deleted Depot Files	View	Show Deleted Depot Files	View>Filter Depot	
Favorite Connections	Settings	Favorite Connections	Connection	
Logout	Settings	Log Off	Connection	
Options...	Settings	Preferences...	Edit	
Port Client User History	Settings	Open Recent	Connection	
Switch Port Client User...	Settings	Open Connection...	Connection	
Set Password for (current user)...	User	Change Password...	Connection	

Next Steps

This guide helps you to start working with files using P4V and points out important basic features, but P4V enables you to do much more: create jobs, branch groups of files, and handle file conflicts that arise in team development settings.

Perforce administrators can perform administrative operations by choosing **Tools > Administration**. Using the Administration tool, superusers can manage users and groups, and their access to files and folders within the depot. Some administrative functions must still be performed using the Perforce command-line client (p4). For details, see the *Perforce Command Reference* and the *Perforce System Administrator's Guide*.

To become expert with P4V:

- Consult the P4V online help and read the Perforce user documentation available from the Perforce Web site.
- Use tooltips.
- Pay attention to the file icons and decorations in the left pane. The decorations and icons display a great deal of information about the type and status of a file.
- Start reading the Log pane.
- Learn drag and drop shortcuts to simplify operations on large sets of files.
- Use P4V views and filtering features to enable you to selectively display information.

To get the whole picture, read the P4V online help, *Introducing Perforce* and the *Perforce System Administrator's Guide*. The guides, which are available from the Perforce web site, describe the full set of features that the Perforce Server provides. Perforce Technical Support is always ready to help you, and there's a thriving community of Perforce users active on the `perforce-users` mailing list. Consult our web site for details.

Next Steps